

Air conduction and diffusion through textile duct

Benelux Premium

Technical Specification Sheet

Textile material 100% polyester

Weight	6.19 oz/yd ²	
Tear strength	Warp	Weft
NMX-A-109-INNTEX-2005	12.92 Lbf	6.54 Lbf
Tensile strength	Warp	Weft
NMX-A-059/2-INNTEX-2008	314.73 Lbf	179.84 Lbf
Permeability	ASTM-D737-04, Value 0.82 CFM/SQFT	
Vertical Flammability	Warp	Weft
ASTM-D-6413-08		
Char length	5.64 in	4.49 in
After flame	3 s	0 s
Flash fire exposure	0,0 s	0,0 s
	Maximum	Minimum
Temperature	140° F	14° F



Benelux Premium is a high-quality permeable material that provides outstanding hygiene results for ventilation systems in industries with environments that require high hygienic standards.

Benelux Premium **helps reduce condensation**. Its polyester fibers are ideal for durable solutions and it is 100% washable. This is the cleanest system that meets the highest hygienic standards due to its antibacterial properties.

Ideal for:

- Food industry
- Pharmaceutical industry
- Laboratories
- Pools
- Malls
- Churches
- Retail
- Showrooms



Additional Information

Additional application

Antistatic
 Flame retardant material
 ASTM-D-6413-08

Recommended use

Internal
 • Air conduction and diffusion



Warranty